



SINATRA

Linear Fire (conventional flue system)

CONTROL OPTIONS



DECORATIVE ACCESSORIES

- Logs, chips & glowing fibers
- White pebbles & gold vermiculite
- Black diamond stones
- Black glass gravel

PROTECTIVE GLASS SCREENS

- Ceramic glass (included)
- Antireflective glass (optional)



Custom length



Gas and CO detectors



Ceramic or antireflective glass

SINATRA

	1200 mm 47.2"	1600 mm 63"	2000 mm 78.7"	2400 mm 94.5"
	(NG) max. 10.3 kW 35 145 BTU/h (LPG) max. 9.5 kW 32 415 BTU/h	(NG) max. 15.0 kW 51 185 BTU/h (LPG) max. 14.3 kW 48 794 BTU/h	(NG) max. 19.7 kW 67 219 BTU/h (LPG) max. 19.0 kW 64 831 BTU/h	(NG) max. 19.8 kW 67 560 BTU/h (LPG) max. 20.0 kW 68 243 BTU/h
	(NG) max. 1.09 m ³ /h 38.5 ft ³ /h (LPG) max. 0.75 kg/h 1.65 lbs/h	(NG) max. 1.58 m ³ /h 55.8 ft ³ /h (LPG) max. 1.12 kg/h 2.47 lbs/h	(NG) max. 2.09 m ³ /h 73.8 ft ³ /h (LPG) max. 1.50 kg/h 3.31 lbs/h	(NG) max. 2.09 m ³ /h 73.8 ft ³ /h (LPG) max. 1.57 kg/h 3.46 lbs/h
	Conventional			
	230 V / [US] 115 V			



FRONT



LEFT FRONT



RIGHT FRONT



LEFT FRONT RIGHT



TUNNEL



ROOM DIVIDER



ISLAND